radwag.com

XA 6.5Y.M.A Microbalance

More information on the website
radwag.com/en/info,w1,0SG



XA 6.5Y.M.A Microbalance

The drawings, photos and graphics used are for illustrative purposes only.

Functions

- Autotest
- Dosing
- Percent Weighing
- Parts counting
- Peak hold
- Formulation
- Newton unit measurement
- Statistics
- Checkweighing
- IR sensors
- GLP Procedures
- Animal weighing
- Pipettes Calibration
- Air density correction
- Automatic sliding door
- Density determination
- Differential weighing
- Ambient conditions monitoring
- Statistical Quality Control
- Packaged Goods Control
- ALIBI Memory
- Wi-Fi

Datasheet

	XA 6.5Y.M.A Microbalance WL-109-0013
Metrological parameters	
Maximum capacity [Max]	6,1 g
Minimum load	0,1 mg
Readability [d]	1 µg
Verification unit [e]	1 mg
Tare range	-6,1 g
Minimum weight (USP)	1,6 mg
Minimum weight (U=1%, k=2)	0,16 mg
Standard repeatability [5% Max]	0,8 µg
Permissible repeatability [5% Max]	1,5 µg
Linearity	±7 µg
Eccentric load deviation	7 µg
Sensitivity time drift	1×10^{-6}/Year×Rt
Stabilization time	~ 3,5 s
Adjustment	internal (automatic)
OIML Class	I
Physical parameters	
Leveling system	automatic – Reflex Level System
Display	10" graphic colour touchscreen
Weighing chamber doors	automatic
Delivery components	Microbalance with an ionizer, weighing pan, weighing pan shield, power supply, brush, fabric dust cover.
Weighing chamber dimensions	199×170×217 mm
Weighing pan dimensions	ø30 mm
Packaging dimensions W x D x H	750×492×595 mm
Net weight	16 kg
Gross weight	20 kg
Construction	
Protection class	IP 43
Communication interface	
Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A Max; 15V DC 2,4A Balance: 12 – 15V DC 1,6A max; 10 – 19W*
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3 °C / 1 h (±1 °C / 8 h)
Relative humidity	40% – 80%
Relative humidity change rate	±1% / h (±4% / 8 h)

Standard repeatability [5% Max] and Standard minimum weight (USP) are parameters obtained in automatic mode under special laboratory conditions. Repeatability is expressed as a standard deviation from 10 cycles of mass standard weighing. Stabilization time dependson the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile. * Power consumption depends on the terminal configuration as well as the number and type of external devices connected. The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

Additional fee for verification

Accessories (Additional Fee)

MediaBox
RFID Tags
Antivibration Tables
Power Adapters
Protective cover for balances
RS 232, RS 485 cables
Additional modules
Anti-Draft Chamber for Microbalances
Professional Weighing Tables
Barcode scanners
Label Printers
THBR 2.0 System - Ambient Conditions Monitoring
Anti-Draft Chamber for XA 4Y and XA 5Y Balances
Weighing dishes
Antistatic ionizer
Receipt Printer
Fingerprint Reader
RS 232 – USB Converter
Under-pan weighing

Software (Additional Fee)

E2R System
Label Editor R02
R-LAB
RADWAG Development Studio
RAD-KEY
RADWAG Remote Desktop
Scales Editor 2.1

Device dimensions W x D x H

XA 6.5Y.M.A Microbalance

